

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of the Claims

1. (Currently Amended) A foot section for a patient support, the foot section including:

a body having a bottom surface, a top surface, a head end portion, and a ~~fix~~ end portion; and

an L-shaped support configured to move in response to movement of the ~~body~~, the L-shaped support having a first portion coupled to the body and a second portion ~~spred~~ apart from the body adjacent to the foot end portion, the second portion maintaining a substantially perpendicular disposition relative to the top surface of the body, and

a second support having an angled portion extending upwardly at an angle relative to the bottom surface of the body.

2. (Currently Amended) The foot section of claim 1, further comprising a ~~second support having wherein the second support has~~ a first portion coupled to the body and a second portion coupled to the L-shaped support.

3. (Original) The foot section of claim 2, wherein the second support includes a first end coupled to the body, a second end coupled to the body, and a middle portion coupled to the L-shaped support.

4. (Currently Amended) The foot section of claim 3, wherein the ~~second support further angled portion~~ includes side portions coupled to the middle portion, the side portions extending upwardly at an angle relative to the bottom surface of the body.

5. (Original) The foot section of claim 4, wherein the angle relative to the bottom surface of the body is substantially equal to 40 degrees.

6. (Original) The foot section of claim 1, wherein the second portion of the L-shaped support includes a first end coupled to the first portion of the L-shaped support and a second end, the top surface of the body including an uppermost surface that lies in a top plane, the top plane is positioned between the first and second ends of the second portion of the L-shaped support.

7. (Original) The foot section of claim 1, wherein the L-shaped support is coupled to the bottom surface of the body.

8. (Original) The foot section of claim 1, further comprising mounting members configured to releasably couple with a frame of the patient support.

9. (Currently Amended) A foot section for a patient support, the foot section including:

a body having a bottom surface, a top surface, a head end portion, and a foot end portion, the top surface of the body including an uppermost surface that lies in a top plane; and

a support fixed relative to the body, the support having a first portion coupled to the body, and a second portion having an upper part spaced-apart from the body adjacent to the foot end portion, and an angled portion extending upwardly at an angle relative to the bottom surface of the body, the top plane of the body being positioned between the first portion and the upper part of the second portion.

10. (Original) The foot section of claim 9, wherein the support is L-shaped.

11. (Currently Amended) A foot section for a patient support, the foot section including:

a body having a bottom surface, a top surface, a head end portion, and a foot end portion, the top surface of the body including an uppermost surface that lies in a top plane; and

a support configured to move with the body, the support having a first portion coupled to the body and a second portion having an upper part spaced-apart from the body adjacent to the foot end portion, the top plane of the body being positioned between the first portion and the upper part of the second portion, the support including a first end coupled to the body, a second end coupled to the body, and a middle portion positioned between the first and second ends, and an angled portion extending upwardly at an angle, the top plane is positioned between the first and second ends and the middle portion.

12. (Currently Amended) The foot section of claim 11, wherein the support angled portion further includes side portions coupled to the middle portion, the side portions extending upwardly at an angle relative to the bottom surface of the body.

13. (Currently Amended) A foot section for a patient support, the foot section including:

a body having a bottom surface, a top surface, a head end portion, and a ~~foot~~ end portion, the top surface of the body including an uppermost surface that lies in a top plane; and

a support configured to move with the body, the support having a first portion coupled to the body and a second portion having an upper part spaced-apart from the body adjacent to the foot end portion, the top plane of the body being positioned between the ~~first~~ portion and the upper part of the second portion, the support including an L-shaped support having a first portion coupled to the body and a second portion, and a second support having a first end coupled to the body, a second end coupled to the body, and a middle portion coupled to the L-shaped support and an angled portion extending upwardly at an angle relative the first portion of the support.

14. (Original) The foot section claim 13, wherein the top plane of the body is positioned between the middle portion of the second support and the first and second ends of the second support.

15. (Original) The foot section of claim 9, further comprising mounting members configured to releasably couple with a frame of the patient support.

16. (Currently Amended) A patient support comprising:

a frame;

a patient support surface coupled to the frame, the patient support surface including a back section, a seat section, and a foot section; and

the foot section including a body having a bottom surface, a top surface having an uppermost surface that lies in a top plane, a head end portion, a foot end portion, and an end support including a bottom portion having an end coupled to the body, an upwardly extending side angled portion coupled to extending upwardly at an angle relative to the bottom portion, and a middle portion coupled to the side portion, the top plane of the body being positioned between the bottom portion and the middle portion.

17. (Currently Amended) The patient support of claim 16, wherein the angled portion includes a side portion which extends upwardly at an angle relative to the bottom surface of the body.

18. (Original) The patient support of claim 17, wherein the angle relative to the bottom surface of the body is substantially equal to 40 degrees.

19. (Original) The patient support of claim 16, wherein the foot section further comprises an L-shaped support having a first portion coupled to the body and a second portion coupled to the middle portion of the end support.

20. (Original) The patient support of claim 19, wherein the second portion of the L-shaped support includes a first end coupled to the first portion of the L-shaped support and a second end, the top plane is positioned between the first and second ends of the second portion of the L-shaped support.

21. (Original) The patient support of claim 16, wherein the foot section further includes mounting members configured to releasably couple with the frame.

22. (Currently Amended) A patient support comprising:

a frame;

a patient support surface supported by the frame, the patient support surface including a back section, a seat section, and a foot section; and

the foot section including a body having a bottom surface, a top surface, a head end portion, a foot end portion, and an L-shaped support having a first portion coupled to the body and a second portion spaced-apart from the body adjacent to the foot end portion, the second portion being substantially perpendicular to the top surface of the body, and a side portion extending at an angle relative to the bottom surface.

23. (Original) The patient support of claim 22, further comprising a second support having a first portion coupled to the body and a second portion coupled to the L-shaped support.

24. (Original) The patient support of claim 23, wherein the second support includes a first end coupled to the body, a second end coupled to the body, and a middle portion coupled to the L-shaped support.

25. (Original) The patient support of claim 22, wherein the second portion of the L-shaped support includes a first end coupled to the first portion of the L-shaped support and a second end, the top surface of the body including an uppermost surface that lies in a top

plane, the top plane is positioned between the first and second ends of the second portion of the L-shaped support.

26. (Original) The patient support of claim 22, wherein the L-shaped support is coupled to the bottom surface of the body.

27. (Original) The patient support of claim 22, wherein the foot section further includes mounting members configured to releasably couple with the frame.

28. (Previously Presented) The foot section of claim 2, wherein the second support includes a first end coupled to the body, a second end coupled to the body, and a middle portion directly coupled to the L-shaped support.

29. (Previously Presented) The patient support of claim 16, wherein the foot section further comprises an L-shaped support having a first portion directly coupled to the body and a second portion directly coupled to the middle portion of the end support.